

Cooling Fan & Blower for Telecommunication

■ PWM speed control / FG / RD function is option.



Model	Rating Voltage (VDC)	Rating Current (Amp)	Power Consumption (Watt)	Speed (RPM)	Air Flow (CFM)	Static Pressure (Inch-H ₂ O)	Noise (dBA)
PSD1204PKB3-A(2).Z.GN	12	0.140	1.68	11000	11.8	0.56	40.0
PSD1204PJBX-A(2).Z.GN	12	1.470	17.64	18000 (IN) 17000 (OUT)	29.8	2.65	66.2
PSD1206PTBX-A(2).U.Z.GN	12	0.355	4.30	8100	36.4	0.64	48.2
PSD1206PMBX-A(2).Z.GN	12	1.500	18.00	14000	69.5	1.98	62.9
PSD4806PMB1-A(2).Z.GN	48	0.250	12.00	12000	56.8	1.46	59.4
PSD1208PHB1-A(2).Z.GN	12	0.194	2.30	3300	39.9	0.18	38.7
PSD1208PTBX-A(2).U.Z.GN	12	0.490	5.90	6200	70.4	0.57	51.3
PSD4808PMBX-A(2).Z.GN	48	0.460	22.10	8000	112.0	1.31	60.5
PSD1209PMBX-A(2).Z.GN	12	2.200	26.40	9500	151.4	2.05	54.3
PSB1297PYB1-AY(2).Z.GN	12	0.560	6.70	3600	26.7	0.76	67.3
PSD1212PTB1-A(2).Z.GN	12	0.825	9.90	4500	147.7	0.62	54.9
PSD1212PLBX-A (2).Z.GN	12	1.850	22.20	4600	189.6	0.79	60.6
PSD4812PTB1-A(2).Z.GN	48	0.218	10.50	4500	147.7	0.62	54.9
PSB1212PLB1-AY(2).Z.GN	12	0.755	9.06	2800	38.7	1.14	55.8
PSD1212PMBX-A(2).Z.GN	12	3.000	36.00	6000	226.5	1.20	65.5

- Specifications are subject to change without notice. Specifications in this catalog are for reference. For more product information, please contact your SUNON sales representative.

热设计网 <http://www.resheji.com>